



## Optional accessories

Anti-Static Duct, Duct Carry Bags.

# EFI75XX

3

YEAR WARRANTY

The **EFI75XX (12"/300mm)** is intended for use in explosive atmospheres. It features a totally enclosed motor and is **IP55** rated. It includes an **ABS**, chemical resistant, anti-static housing and integral thermal overload protection.

## IECEx and ATEX certification

Safety of your workers is a priority. This unit is certified for use in Group IIB, Zone 1, T6 hazardous atmospheres.

## Virtually indestructible

These units are made extra tough to work alongside your team in harsh areas. They are built with a durable housing designed to withstand industrial workspace environments. ABS anti-static casing is flame retardant and chemical resistant.

## Duct adapters and cord

This unit includes two integrated duct adapters, and a handy 7.6m extended reach power cord as standard.

## Secure starters

The starter is secured in the flameproof motor enclosure. This prevents the risk of any ignition when the unit is powered to ensure safety of workers in hazardous environments. Use the pull switch to activate the ventilator.

## Thermal switch

Integral thermal overload protection comes standard with the unit. This prevents damage to the ventilators from overheating.

## Hazardous Certification

IECEx UL certificate number 13.0062X

| Model<br>Order code        | EFI75XX<br>EB7201XX-230 |
|----------------------------|-------------------------|
| Free air                   | 4,250m³/hr              |
| Motor                      | 0.75hp (0.56 kW)        |
| Unit rating                | IP55                    |
| Power supply               | 230V/w50Hz              |
| Amps                       | 3A                      |
| Weight                     | 20kg                    |
| Equipment Protection Level | Ex d e                  |

