



# EFI120XX | EFI150XX

3

YEAR WARRANTY

Engineered to move high volumes of air, the EFI120XX and EFI150XX (16"/400mm) can be used for both exhaust or supply air requirements. They feature a totally enclosed motor for use in hazardous locations and an ABS anti-static casing that is flame retardant and chemical resistant.

## IECEX and ATEX certification

Safety of your workers is a priority. This unit is certified for use in Group IIB, Zone 1, T6 hazardous atmospheres

## Virtually indestructible

These units are made extra tough to work alongside your team in harsh areas. They are built with a durable housing designed to withstand industrial workspace environments. ABS anti-static casing is flame retardant and chemical resistant.

## Easy storage

This unit is designed to be stackable for convenient storage. Rubber grips on the base create extra stability when in use. Transporting the unit is easy with handles for controlled manoeuvring.

## Duct adapters and power cord

This unit includes two integrated duct adapters and a handy 7.6m long power cord for convenience.

## Hazardous Certification

IECEX UL certificate number 13.0062X

Model Order Code	EFI120XX EA8120XX	EFI150XX EG8200XX-230
Free air	6,375m³/hr	7,580m³/hr
Motor	1.2hp (0.9 kW)	1.5hp (1.1 kW)
Unit Rating	IP55	IP55
Power Supply	240V/50Hz	230V/50Hz
Amps	5A	8A
Weight	25kg	28kg
Equipment Protection Level	Ex d e	

