



How the SS series Air Curtains work

SS SERIES AIR CURTAINS

3
YEAR WARRANTY

IP55
MOTOR IP RATING

The SS Series Air Curtains are designed and manufactured in Australia to withstand the most demanding environments. They are engineered to efficiently create a wall of air across door openings.

Washdown for easy cleaning

The SS Series Air Curtains include a range of hygiene critical features. Its IP55 rated motor can withstand water from high pressure cleaning without impairing performance.

Low noise level

The SS Series Air Curtains are packed with a powerful 415V/0.75kW motor. They have been engineered to keep noise levels to a minimum.

Stainless steel casing

All stainless steel casing is suitable for extremely corrosive environments. Comes with a 3 year warranty as standard.

Keep insects dust and dirt out

Our Air Curtains create a wall of air across door openings that prevent unwanted flying insects and contaminants, such as dust and dirt particles, from entering the building. Optimal work conditions and reduced cleaning times are achieved as a result.

Comes in three sizes

Available in 980mm, 1280mm and 1580mm sizes. Units are designed to fit above standard industry doorways that have limited space. The installation process is simple, meaning these units can be fitted quickly across large sites.

Model	SSAC900	SSAC1200	SSAC1500
Overall length (Including mounting bracket)	980mm	1280mm	1580mm
Depth	300mm		
Overall height	300mm		
Fixing centres	940mm	1240mm	1540mm
Outlet grille	90x1170mm		
Power Supply/ Motor	415V/0.75kW		
Weight	35kg	40kg	45kg
Outlet velocity	26m/s		
Avg. dB(A)@3M	67	70	71



All our Air Curtains comply with AQIS Standards

The AQIS compliance requirements for an Air Curtain is that it must provide a minimum of 8.0 meters per second air velocity measured 900mm above floor level.

Contact our office for more information about AQIS compliant Air Curtains and models we have to offer.