



ECONOMYARM

FLEXIBLE EXTRACTION ARM

360°
ROTATION

DETACHABLE
HOOD

The Plymovent 'EA' extraction arm provides flexibility and efficiency when used with a fume extraction system. It is suitable when extracting dust, welding fumes, oil mist and fumes from solvents.

- Lower spring assisted joint is supported in a double ball-bearing mount and gives the EA-S a smooth and flexible movement.
- 360° ring handle allows ease of reach and access from any position.
- Arm has a sturdy spring balanced internal support mechanism.
- Hood can be turned 110° in all directions.
- Detachable hood allows for attachment of an extension hose (SLE-30).
- Suitable for MIG-MAG/GMAW welding, TIG welding, FCAW welding and stick/MMAW welding.
- Flame resistant PVC hose.
- 360° rotatable arm ensures easy manoeuvrability within the work space.
- Hood is fitted with a safety mesh and shut-off damper.
- Recommended for light welding activities.

PRODUCT CODE	PLY-EA-2..	PLY-EA-3..	PLY-EA-4..
Max. Working Radius	2m	3m	4m
Material	Flame-retardant PVC reinforced with spring steel wire		
Tube Diameter	160mm	160mm	160mm
Hood Diameter	300mm	300mm	300mm
Recommended Air Flow m³/hr	800-1200		
Weight (kg)	14.5(S) 17.5(H)	16.5(S) 21(H)	20(S) 23(H)

Add S to end of code for standing model.
Add H to end of code for hanging model.