



How the SS series Air Curtains work



SS SERIES

AIR CURTAINS



The SS Series Air Curtains are designed and manufactured in Australia to withstand the most demanding environments. They are engineered to efficiently create a wall of air across door openings.

- IP55 rated motor can withstand water from high pressure cleaning without impairing performance.
- Engineered to keep noise levels to a minimum.
- All stainless steel casing is suitable for extremely corrosive environments.
- Prevents unwanted flying insects and contaminants, such as dust and dirt particles, from entering the building.
- Available in 980mm, 1280mm and 1580mm sizes.
- Designed to fit across standard industry doorways with limited space.
- Fitted with adjustable air direction vanes.

COMPLIES WITH AQIS STANDARDS

The AQIS compliance requirements for an Air Curtain is that it must provide a minimum of 8.0 meters per second air velocity measured 900mm above floor level.

Contact our office for more information about AQIS compliant Air Curtains and models we have to offer.

MODEL	SSAC900	SSAC1200	SSAC1500
OVERALL LENGTH (INCLUDING MOUNTING BRACKET)	980mm	1280mm	1580mm
DEPTH	300mm		
OVERALL HEIGHT	300mm		
FIXING CENTRES	940mm	1240mm	1540mm
OUTLET GRILLE	90x1170mm		
POWER SUPPLY/ MOTOR	415V/0.75kW		
WEIGHT	35kg	40kg	45kg
OUTLET VELOCITY	26m/s		
AVG. dB(A) @3M	67	70	71